

Lencore

THE LEADING MANUFACTURER OF SOUND MASKING SYSTEMS.

A GREAT SOUND MAKES NO NOISE®

LENCORE SPECTRA – i.NET™ SOUND MASKING SYSTEM

Standard Speaker Enclosure Specifications – Model G19/G85

What makes Lencore's new Spectra i.Net™ system intelligent is its intuitive technology and its infinite flexibility on an open-platform system to suit any project size. The combined innovations of the complete sound masking system – sound source, speakers, power supply; i.LON®, music page interface, equalizers, online Sound Manager control and one-touch remote control put the Spectra i.Net™ system on a new level of customization and performance.

The Spectra i.Net™ system is the most sophisticated masking system available when a network system is required. The system features fast, complete control over every sound frequency for masking. Extreme design flexibility, plus, easy system expansion with the addition of sound sources and speakers to the network. Sound control with the click of the remote or mouse, even off-site. Preferred, award-winning sound quality, only from Lencore's Systems.

Speakers are configured with integrated RJ12 connections for plug & play and ease of installation.



Masking/Paging Units are UL listed for use in air-handling spaces.

TECHNICAL SPECIFICATIONS

Speaker Enclosure:

Aluminum Housing
Galvanized Perforated Grill
Lightweight Mounting Chain
Two speaker size available: 6" & 4"

Height:

6" G19 4" G85

Diameter:

6" G19 6" G85

Weight::

3 lbs. G19 3 lbs. G85

Loudspeaker:

5-inch wide dispersion
Power Rating: 10 watts RMS
Frequency Response:
50 – 12,000 Hz
Impedance: 32 Ohms
Resonance: 80 Hz
Magnet Weight: 10 oz.
Magnet Structure Weight: 26 oz.
Cone: Formed Fiber
Cone Suspension: High Compliance Foam
Voice Coil: 1-inch diameter
Voice Coil Form: Anodized Aluminum

General Specifications:

Paging Input: via OP and MPI
Power Requirement: Powered by OP
Output Adjustment: N/A

Speaker Wire Requirements:

All wire must be plenum rated and UL listed.
Speakers use Cat 5e or equivalent, 3 twisted pair and RJ12 connectors.
Crossover wire: Pin 1 to Pin 6, Pin 2 to Pin 5, etc.

Other System Wire Requirements:

16 gauge, plenum rated, stranded, 2-conductor wire (for power supply to OP).

Cat 5e cable, 3 twisted pair, with standard RJ12 connectors.

- 3 twisted pair (audio cable and speaker cable)

Masking/Paging Units are UL Listed
for use in air handling spaces

Other Systems Also Available

Spectra i.Net™ (Networked) Spectra® CrossNetOne™ (Networked),
CrosswaysOne™

In-plenum and direct field
all available with paging/music.